

# DEVELON

Europe

## Full liner



# MINI EXCAVATORS



**DX10Z**



**DX17Z**

<b>Operating weight</b>	kg	1200	1749
<b>Engine power</b>	hp/kW @ rpm	9.9/7.4 @ 2000	13.3/9.9 @ 2500
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.025	0.03



**DX50Z-7**



**DX55R-7**



**DX62R-3**

	5438	5740	6250
	48.8/36.6 @ 2200	48.8/36.6 @ 2200	59.4/44.3 @ 2100
	0.16	0.16	0.175

		<b>DX10Z</b>	<b>DX17Z</b>	<b>DX19</b>	<b>DX27Z-7</b>
<b>Operating weight</b>	kg	1200	1749	1900	2705
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.025	0.03	0.065	0.08
<b>Travel speed</b>	km/h	2.1 - 3.1	2.5 - 4.0	2.5 - 4.0	2.5 - 4.3
<b>Engine model</b>	-	Kubota D722-E2B-BCZ-6	Kubota D722-E2B-BCZ-6	Kubota D722-E2B-BCZ-7	Develon D17
<b>Power</b>	hp/kW @ rpm	9.9/7.4 @ 2000	13.3/9.9 @ 2500	13.3/9.9 @ 2500	24.8/18.4 @ 2400
<b>Emission standard</b>	-	Stage V	Stage V	Stage V	Stage V
<b>Digging reach</b>	mm	3145	3971	4257	4655
<b>Digging depth</b>	mm	1820	2249	2565	2645
<b>Digging height</b>	mm	2685	3378	3701	2935
<b>Length</b>	mm	2793	3450	3812	4191
<b>Width</b>	mm	1100 (710)	1360	1360 (980)	1550
<b>Height</b>	mm	2209	2297	2299	2448



**DX19**

1900

13.3/9.9 @ 2500

0.065



**DX27Z-7**

2705

24.8/18.4 @ 2400

0.08



**DX35Z-7**

3499

24.8/18.4 @ 2400

0.11



**DX63-3**

6370

59.4/44.3 @ 2100

0.175



**DX85R-7**

9520

65/48.5 @ 2100

0.28

<b>DX35Z-7</b>	<b>DX50Z-7</b>	<b>DX55R-7</b>	<b>DX62R-3</b>	<b>DX63-3</b>	<b>DX85R-7</b>
3499	5438	5740	6250	6370	9520
0.11	0.16	0.16	0.175	0.175	0.28
2.6 - 4.7	2.6 - 4.4	2.6 - 4.4	2.6 - 4.7	2.6 - 4.7	2.7 - 4.7
Develon D17	Develon D18	Develon D18	Yanmar 4TNV98	Yanmar 4TNV98	Develon D24
24.8/18.4 @ 2400	48.8/36.4 @ 2200	48.8/36.4 @ 2200	59.4/44.3 @ 2100	59.4/44.3 @ 2100	65/48.5 @ 2100
Stage V	Stage V	Stage V	Stage V	Stage V	Stage V
5355	5945	6090	6525	6355	7530
3275	3480	3630	4115	4115	4665
3580	5575	5680	6005	6005	7035
4760	5386	5400	5670	5685	6265
1700	1980	1980	1980	1980	2250
2479	2575	2575	2550	2550	2657

# WHEELED EXCAVATORS



**DX57W-7**

**DX100W-7**

<b>Operating weight</b>	kg	5800	10700
<b>Engine power</b>	hp/kW @ rpm	52.3/42.5 @ 2400	100/75 @ 2000
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.175	0.3



**DX165W-7**



**DX170W-7**

	17400 - 18900	17700 - 19300
	137/102 @ 2200	152/113 @ 2000
	0.7	0.75

		<b>DX57W-7</b>	<b>DX100W-7</b>	<b>DX140W-7</b>
<b>Operating weight</b>	kg	5800	10700	15800 - 17000
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.175	0.3	0.6
<b>Travel speed</b>	km/h	10 - 30	5.4 - 37.4	3.5 - 37
<b>Engine model</b>	-	Develon D24	Develon D34	Develon DLo6V
<b>Power</b>	hp/kW @ rpm	52.3/42.5 @ 2400	100/75 @ 2000	137/103 @ 2000
<b>Emission standard</b>	-	Stage V	Stage V	Stage V
<b>Digging reach</b>	mm	6108	7820	7585
<b>Digging depth</b>	mm	3495	4245	4490
<b>Digging height</b>	mm	5976	8265	8195
<b>Length</b>	mm	5896	5713	8043
<b>Width</b>	mm	1947	2450	2495
<b>Height</b>	mm	2861	3011	3052
<b>Arm length</b>	mm	1600	2250	2100



### DX140W-7

15800 - 17000  
137/103 @ 2000  
0.6



### DX160W-7

17500 - 18100  
137/103 @ 2000  
0.7



### DX190W-7

18320 - 20410  
174/130 @ 1900  
0.8



### DX210W-7

21900 - 23000  
189/141 @ 1900  
0.9

#### DX160W-7

#### DX165W-7

#### DX170W-7

#### DX190W-7

#### DX210W-7

17500 - 18100	17400 - 18900	17700 - 19300	18320 - 20410	21900 - 23000
0.7	0.7	0.75	0.8	0.9
3.5 - 37	3 - 34	3.0 - 37	3.5 - 37	4.0 - 35
Develon DLo6V	Perkins 1204J	Develon DLo6V	Develon DLo6V	Develon DLo6V
137/103 @ 2000	137/102 @ 2200	152/113 @ 2000	174/130 @ 1900	189/141 @ 1900
Stage V	Stage V	Stage V	Stage V	Stage V
8235	8235	8875	9255	9980
5020	5020	5315	5725	6160
8850	8850	9140	9440	10140
8205	8205	8644	8867	9477
2495	2490	2530	2530	2530
3052	3102	3087	3131	3155
2500	2500	2500	2600	3000

# CRAWLER EXCAVATORS



**DX140LCR-7**

**DX140LC-7**

<b>Operating weight</b>	kg	15500	14400
<b>Engine power</b>	hp/kW @ rpm	115/86 @ 2000	115/86 @ 2000
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.75	0.75



**DX210LC-7**

**DX210NLC-7**

	21700	21700
	166/124 @ 1800	166/124 @ 1800
	1.2	1.2

**DX140LCR-7**

**DX140LC-7**

**DX160LC-7HT**

<b>Operating weight</b>	kg	15500	14400	16800
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.75	0.75	0.8
<b>Travel speed</b>	km/h	2.9 - 4.7	2.9 - 4.7	2.3 - 3.7
<b>Engine model</b>	-	Develon G2 D34	Develon G2 D34	Develon G2 D34
<b>Power</b>	hp/kW @ rpm	115/86 @ 2000	115/86 @ 2000	115/86 @ 2000
<b>Emission standard</b>	-	Stage V	Stage V	Stage V
<b>Digging reach</b>	mm	8285	8285	8285
<b>Digging depth</b>	mm	5485	5635	5635
<b>Digging height</b>	mm	9265	8660	8660
<b>Length</b>	mm	7360	7685	7685
<b>Width</b>	mm	2590	2590	2590
<b>Height</b>	mm	2835	2785	2785
<b>Arm length</b>	mm	2500	2500	2500



### DX160LC-7HT

16800  
115/86 @ 2000  
0.8



### DX210-7

21300  
166/124 @ 1800  
1.1



### DX225LC-7X

23300  
174/129 @ 1800  
1.3



### DX235LC-7

23000  
174/129 @ 1800  
1.4

#### DX210-7

#### DX210LC-7

#### DX210NLC-7

#### DX225LC-7X

#### DX235LC-7

21300	21700	21700	23300	23000
1.1	1.2	1.2	1.3	1.4
3.2 - 5.9	3.2 - 5.9	3.2 - 5.9	3.1 - 5.5	3.0 - 5.3
Develon DLo6V	Develon DLo6V	Develon DLo6V	Develon DLo6V	Develon DLo6V
166/124 @ 1800	166/124 @ 1800	166/124 @ 1800	174/129 @ 1800	174/129 @ 1800
Stage V	Stage V	Stage V	Stage V	Stage V
9535	9535	9535	9865	9895
6270	6270	6270	6590	6595
9330	9330	9330	9620	9555
9445	9445	9445	9570	9522
2800	2990	2540	2990	2990
3139	3139	3139	3005	3139
2600	2600	2600	2900	2900

# CRAWLER EXCAVATORS



**DX235LCR-7 DX245NHD-7**

<b>Operating weight</b>	kg	24300	25100
<b>Engine power</b>	hp/kW @ rpm	174/129 @ 1800	174/129 @ 1800
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	1.4	1.3



**DX350LC-7**

**DX380LC-7**

	40200	43500
	285.6/213 @ 1800	326/240 @ 1800
	1.85	2.0

**DX235LCR-7 DX245NHD-7 DX255LC-7**

<b>Operating weight</b>	kg	24300	25100	25700
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	1.4	1.3	1.5
<b>Travel speed</b>	km/h	3.2 - 5.8	3.0 - 5.3	3.2 - 5.6
<b>Engine model</b>	-	Develon DLo6V	Develon DLo6V	Develon DLo6V
<b>Power</b>	hp/kW @ rpm	174/129 @ 1800	174/129 @ 1800	189/141.3 @ 1900
<b>Emission standard</b>	-	Stage V	Stage V	Stage V
<b>Digging reach</b>	mm	9830	9465	10175
<b>Digging depth</b>	mm	6680	6095	6810
<b>Digging height</b>	mm	10805	9450	9705
<b>Length</b>	mm	8970	9566	10080
<b>Width</b>	mm	2990	2540	3000 - 3200
<b>Height</b>	mm	3123	3190	3200
<b>Arm length</b>	mm	2900	2400	3000





### DX255LC-7

25700  
189/141.3 @ 1900  
1.5



### DX300LC-7

31500  
271/202 @ 1800  
1.7



### DX420LC-7

43500  
344.4/257 @ 1800  
2.2



### DX490LC-7

50400  
394/294 @ 1800  
3.0

#### DX300LC-7

#### DX350LC-7

#### DX380LC-7

#### DX420LC-7

#### DX490LC-7

31500

40200

43500

43500

50400

1.7

1.85

2.0

2.2

3.0

3.0 - 5.5

3.5 - 5.7

3.0 - 5.4

3.2 - 5.3

3.2 - 5.6

Develon DLo8V

Develon DLo8V

Scania DC09

Scania DC13

Scania DC13

271/202  
@ 1800

285.6/213  
@ 1800

326/240  
@ 1800

344.4/257  
@ 1800

394/294  
@ 1800

Stage V

Stage V

Stage V

Stage V

Stage V

10725

10980

11170

11430

12125

7305

7540

7415

7635

7790

10325

10325

10435

10615

11050

10605

11350

11285

11740

12230

3000 - 3200

3000 - 3280

3000 - 3350

3350

2990 - 3490  
3340 - 3900

3050

3390

3415

3355

3350

3100

3200

3200

3250

3350

# CRAWLER EXCAVATORS



**DX530LC-7**

<b>Operating weight</b>	kg	52900
<b>Engine power</b>	hp/kW @ rpm	394/294 @ 1800
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	3.3



**DX800LC-7**

	79500
	539/402 @ 2100
	2.9 - 4.8



**DX1000LC-7**

	99500
	629/469 @ 2000
	3.2 - 5.6

## DX530LC-7    DX800LC-7    DX1000LC-7

		DX530LC-7	DX800LC-7	DX1000LC-7
<b>Operating weight</b>	kg	52900	79500	99500
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	3.3	4.6	6.8
<b>Travel speed</b>	km/h	3.2 - 5.6	2.9 - 4.8	3.2 - 5.6
<b>Engine model</b>	-	Scania DC13	Perkins 2506	Perkins 2806
<b>Power</b>	hp/kW @ rpm	394/294 @ 1800	539/402 @ 2100	629/469 @ 2000
<b>Emission standard</b>	-	Stage V	Stage V	Stage V
<b>Digging reach</b>	mm	10735	11250	12430
<b>Digging depth</b>	mm	6755	6685	7260
<b>Digging height</b>	mm	9630	10700	12425
<b>Length</b>	mm	11530	12230	11530
<b>Width</b>	mm	2990 - 3490 3340 - 3900	3400 - 4000	3440 - 4200
<b>Height</b>	mm	3350	3540	3615
<b>Arm length</b>	mm	2900	3350	2900

# WHEEL LOADERS



## DL200-7

<b>Operating weight</b>	kg	12047
<b>Engine power</b>	hp/kW @ rpm	144/106 @ 2200
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	2.0



## DL220-7

	13300
	160/119 @ 2100
	2.3



## DL250-7

	13900
	172/128 @ 2100
	2.5

		DL200-7	DL220-7	DL250-7
<b>Operating weight</b>	kg	12047	13300	13900
<b>Bucket range (GP)</b>	m <sup>3</sup>	1.9 - 2.2	2.2 - 2.5	2.4 - 2.7
<b>Engine model</b>	-	Perkins 1204J	Develon DLo6	Develon DLo6
<b>Power</b>	hp/kW @ rpm	144/106 @ 2200	160/119 @ 2100	172/128 @ 2100
<b>Emission standard</b>	-	Stage V	Stage V	Stage V
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	2.0	2.3	2.5
<b>Tipping load (straight/full turn at 40°)</b>	kg	10124/8933	10652/9383	11015/9696
<b>Max. dump height on pivot</b>	mm	3716	3853	3853
<b>Breakout force</b>	kN	98	97	116
<b>Maximum speed</b>	km/h	40	40	40
<b>Turning radius at bucket</b>	mm	5414	6016	6115
<b>Tires</b>	-	20.5 R25	20.5 R25	20.5 R25
<b>Length</b>	mm	7208	7458	7487
<b>Width – at tires edge</b>	mm	2539	2539	2539
<b>Height</b>	mm	3313	3313	3313

# WHEEL LOADERS



**DL280-7**

**DL320-7**

<b>Operating weight</b>	kg	15562	19493
<b>Engine power</b>	hp/kW @ rpm	190/141 @ 2000	271/202 @ 1800
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	2.8	3.3



**DL420CVT-7**

**DL480-7**

	23419	26444
	326/240 @ 1800	345/257 @ 1800
	4.3	4.8

		<b>DL280-7</b>	<b>DL320-7</b>	<b>DL380-7</b>
<b>Operating weight</b>	kg	15562	19493	20269
<b>Bucket range (GP)</b>	m <sup>3</sup>	2.7 - 2.9	3.3 - 3.8	3.7 - 4.0
<b>Engine model</b>	-	Develon DLo6	Develon DLo8	Develon DLo8
<b>Power</b>	hp/kW @ rpm	190/141 @ 2000	271/202 @ 1800	271/202 @ 1800
<b>Emission standard</b>	-	Stage V	Stage V	Stage V
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	2.8	3.3	3.7
<b>Tipping load (straight/full turn at 40°)</b>	kg	12247/10765	15948/14079	16248/14341
<b>Max. dump height on pivot</b>	mm	3934	4175	4175
<b>Breakout force</b>	kN	140	170	181
<b>Maximum speed</b>	km/h	40	40	40
<b>Turning radius at bucket</b>	mm	6182	6748	6797
<b>Tires</b>	-	20.5 R25	23.5 R25	23.5 R25
<b>Length</b>	mm	7669	8530	8530
<b>Width – at tires edge</b>	mm	2649/2550*	2845	2845
<b>Height</b>	mm	3360	3511	3511

\* narrow rims



### DL380-7

20269  
271/202 @ 1800  
3-7



### DL420-7

23419  
345/257 @ 1800  
4-3



### DL550-7

33209  
380/283 @ 1800  
5-4



### DL580-7

34311  
400/294 @ 1800  
6.0

DL420-7	DL420CVT-7	DL480-7	DL550-7	DL580-7
23419	23419	26444	33209	34311
4.3 - 4.5	4.3 - 4.9	4.8 - 5.0	5.4 - 5.9	6.0 - 6.6
Scania DC13	Scania DC09	Scania DC13	Scania DC13	Scania DC13
345/257 @ 1800	326/240 @ 1800	345/257 @ 1800	380/283 @ 1800	400/294 @ 1800
Stage V	Stage V	Stage V	Stage V	Stage V
4-3	4-3	4-8	5-4	6-0
19351/ 17071	19351/ 17071	20717/ 18282	24830/ 21897	27355/ 24315
4265	4265	4519	4806	4996
183	183	224	230	264
40	40	40	40	40
7065	7065	7352	7573	7596
26.5 R25	26.5 R25	26.5 R25	29.5 R25	29.5 R25
9138	9138	9454	9885	10059
2982	2982	3095	3289	3289
3660	3660	3635	3863	3863

# COMPACT WHEEL LOADERS



## DL60-7

<b>Operating weight</b>	kg	3750
<b>Engine power</b>	hp/kW	66/48.5
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.6



## DL80TL-7

		5200
		75/55
		0.9

		DL60-7	DL65-7
<b>Operating weight</b>	kg	3750	3650
<b>Bucket range (GP)</b>	m <sup>3</sup>	0.4 - 1.2	0.4 - 1.2
<b>Engine model</b>	-	Kubota V2403	Kubota V2403
<b>Power</b>	hp/kW	66/48.5	66/48.5
<b>Emission standard</b>	-	Stage V	Stage V
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.6	0.6
<b>Tipping load (straight/full turn at 40°)</b>	kg	1685	2200
<b>Max. dump height on pivot</b>	mm	2450	1800
<b>Maximum speed</b>	km/h	30	30
<b>Tires</b>	-	11.5/80 - 15.3	11.5/80 - 15.3
<b>Length</b>	mm	4660	4595
<b>Width – at tires edge</b>	mm	1340	1340
<b>Height</b>	mm	2275	2275



### DL65-7

3650

66/48.5

0.6



### DL80-7

5200

75/55

0.9



### DL85-7

5100

75/55

0.9

### DL80-7

5200

0.6 - 2.0

Kubota V3307

75/55

Stage V

0.9

2455

2551

20 - 35

11.5/80 - 15.3

5002

1460

2523

### DL80TL-7

5200

0.6 - 2.0

Kubota V3307

75/55

Stage V

0.9

2680

3400

20 - 35

11.5/80 - 15.3

5310

1460

2523

### DL85-7

5100

0.6 - 2.0

Kubota V3307

75/55

Stage V

0.9

2876

1919

20 - 35

11.5/80 - 15.3

4993

1460

2523

# ARTICULATED DUMP TRUCKS

<b>Maximum payload</b>	kg
<b>Maximum power (ISO 3046)</b>	kW @ rpm
<b>Body capacity heaped (without/with tailgate)</b>	m <sup>3</sup>



## DA45-7

	41000
	368 @ 2100
	24.4/26.1

## DA30-7

<b>Speeds - forward</b>	km/h	6 - 8 - 11 - 16 - 23 - 32 - 45 - 55
<b>Speeds - reverse</b>	km/h	6 - 8 - 11 - 16
<b>Engine model</b>	-	Scania DC9
<b>Power</b>	kW @ rpm	276 @ 2100
<b>Emission standard</b>	-	Stage V
<b>Transmission model</b>	-	ZF 8 EP320
<b>Weight empty front/rear axle</b>	kg	12700/10500
<b>Weight loaded front/rear axle</b>	kg	15872/35328
<b>Net weight</b>	kg	23200
<b>Length</b>	mm	9534
<b>Width</b>	mm	2967
<b>Total height</b>	mm	3560





### DA30-7

28000

276 @ 2100

16.8/17.8



### DA45-7 4X4

41000

368 @ 2100

25.7

#### DA45-7

#### DA45-7 4X4

5 · 8 · 11 · 16 · 23 · 32 · 45 · 55

5 · 8 · 11 · 16 · 23 · 32 · 45 · 55

5 · 8 · 11 · 16

5 · 8 · 11 · 16

Scania DC13

Scania DC13

368 @ 2100

368 @ 2100

Stage V

Stage V

ZF 8 EP420

ZF 8 EP420

14200/15900

14500/16000

22041/49059

22165/49335

30100

30500

10590

10187

3475

3990

3850

3850

# MATERIAL HANDLERS



<b>Material Handler</b>		<b>DX230WMH-7 Gooseneck Arm</b>	<b>DX230WMH-7 Straight Arm</b>
<b>Operating weight</b>	kg	24017	24317
<b>Travel speed</b>	km/h	4 - 9 - 20	4 - 9 - 20
<b>Engine model</b>	-	Develon DLo6V	Develon DLo6V
<b>Power (SAE J1995)</b>	hp/kW @ rpm	189/141 @ 1900	189/141 @ 1900
<b>Emission standard</b>	-	Stage V	Stage V
<b>Max. bucket pin height</b>	mm	11400	11600
<b>Max. working reach</b>	mm	10000	10000
<b>Max. working depth</b>	mm	4300	4000
<b>Boom Length</b>	mm	6100	6100
<b>Arm Length</b>	mm	4200	4000
<b>Min. swing radius</b>	mm	2700	2700
<b>Elevating height</b>	mm	2500	2500



## Material Handler

### DX250WMH-7 Gooseneck Arm

### DX250WMH-7 Straight Arm

<b>Operating weight</b>	kg	25397	25672
<b>Travel speed</b>	km/h	4 - 9 - 20	4 - 9 - 20
<b>Engine model</b>	-	Develon DLo6V	Develon DLo6V
<b>Power (SAE J1995)</b>	hp/kW @ rpm	189/141 @ 1900	189/141 @ 1900
<b>Emission standard</b>	-	Stage V	Stage V
<b>Max. bucket pin height</b>	mm	12100	11900
<b>Max. working reach</b>	mm	10700	10400
<b>Max. working depth</b>	mm	4700	4100
<b>Boom Length</b>	mm	6500	6500
<b>Arm Length</b>	mm	4500	4000
<b>Min. swing radius</b>	mm	2700	2700
<b>Elevating height</b>	mm	2500	2500

# DEMOLITION



<b>Demolition</b>		<b>DX245DM-7 HRD</b>	<b>DX245DM-7 Digging</b>
<b>Operating weight</b>	kg	30800	28900
<b>Travel speed</b>	km/h	3.0 - 5.5	3.0 - 5.5
<b>Engine model</b>	-	Develon DLo6P	Develon DLo6P
<b>Power (SAE J1995)</b>	hp/kW @ rpm	173/129 @ 1800	173/129 @ 1800
<b>Emission standard</b>	-	Stage V	Stage V
<b>Pin reach</b>	mm	12900	8170
<b>Pin depth</b>	mm	N/A	4785
<b>Pin height</b>	mm	18070	8155
<b>Overall length</b>	mm	11460	9590
<b>Width superstructure</b>	mm	2540	2540
<b>Variable undercarriage width</b>	mm	2540 ~ 3740	2540 ~ 3740
<b>Overall height</b>	mm	3150	3150



<b>Demolition</b>		<b>DX380DM-7 HRD</b>	<b>DX380DM-7 Digging</b>
<b>Operating weight</b>	kg	47400	44800
<b>Travel speed</b>	km/h	3.0 - 5.4	3.0 - 5.4
<b>Engine model</b>	-	Scania DCo9	Scania DCo9
<b>Power (SAE J1995)</b>	hp/kW @ rpm	327/240 @ 1800	327/240 @ 1800
<b>Emission standard</b>	-	Stage V	Stage V
<b>Pin reach</b>	mm	14500	10200
<b>Pin depth</b>	mm	N/A	5500
<b>Pin height</b>	mm	23000	9200
<b>Overall length</b>	mm	15200	11285
<b>Width superstructure</b>	mm	2990	2990
<b>Variable undercarriage width</b>	mm	2970 ~ 4370	2970 ~ 4370
<b>Overall height</b>	mm	3148	3148

# DEMOLITION



<b>Demolition</b>		<b>DX530DM-7 HRD</b>	<b>DX530DM-7 Digging</b>
<b>Operating weight</b>	kg	60500	56800
<b>Travel speed</b>	km/h	3.1 - 5.5	3.1 - 5.5
<b>Engine model</b>	-	Scania DC13	Scania DC13
<b>Power (SAE J1995)</b>	hp/kW @ rpm	394/294 @ 1800	394/294 @ 1800
<b>Emission standard</b>	-	Stage V	Stage V
<b>Pin reach</b>	mm	16500	10300
<b>Pin depth</b>	mm	N/A	5965
<b>Pin height</b>	mm	27500	9690
<b>Length</b>	mm	18500	12230
<b>Width</b>	mm	2990	2990
<b>Variable undercarriage width</b>	mm	2970 ~ 4370	2970 ~ 4370
<b>Height</b>	mm	3360	3360



## Demolition

### DX530DM-7 HRD (Special version)

### DX530DM-7 Digging (Special version)

		DX530DM-7 HRD (Special version)	DX530DM-7 Digging (Special version)
<b>Operating weight</b>	kg	70500	63000
<b>Travel speed</b>	km/h	3.1 - 5.5	3.1 - 5.5
<b>Engine model</b>	-	Scania DC13	Scania DC13
<b>Power (SAE J1995)</b>	hp/kW @ rpm	394/294 @ 1800	394/294 @ 1800
<b>Emission standard</b>	-	Stage V	Stage V
<b>Pin reach</b>	mm	18000	10300
<b>Pin depth</b>	mm	N/A	5965
<b>Pin height</b>	mm	31000	9690
<b>Length</b>	mm	22300	12230
<b>Width</b>	mm	2990	2990
<b>Variable undercarriage width</b>	mm	2970 ~ 4370	2970 ~ 4370
<b>Height</b>	mm	3360	3360

# SPECIAL APPLICATION



## SLR and Semi-SLR

## DX225LC-7 SLR

<b>Operating weight</b>	kg	24600
<b>Bucket capacity (SAE)</b>	m <sup>3</sup>	0.39
<b>Travel speed</b>	km/h	3.1 - 5.5
<b>Engine model</b>	-	Develon DLo6V
<b>Power</b>	hp/kW @ rpm	174/129 @ 1800
<b>Emission standard</b>	-	Stage V
<b>Digging reach</b>	mm	15365
<b>Digging depth</b>	mm	11660
<b>Digging height</b>	mm	13045
<b>Length</b>	mm	12390
<b>Width</b>	mm	3190
<b>Height</b>	mm	3385





### DX300LC-7 SLR

### DX530LC-7 Semi SLR

### DX530LC-7 SLR

33000	51900	52200
0.64	1.27	0.92
3.0 - 5.5	3.2 - 5.6	3.2 - 5.6
Develon DLo8P	Scania DC13	Scania DC13
271/202 @ 1800	394/294 @ 1800	394/294 @ 1800
Stage V	Stage V	Stage V
17510	16060	19615
13780	11795	15125
14195	12755	14435
14320	14155	16195
3400	3340 - 3900	3340 - 3900
3475	3910	4070

# ATTACHMENTS

## DO IT ALL!

Range of Develon Buckets, Breakers, Quick Couplers, Pallet Forks and more...

For: Develon wheel loaders, crawler and wheeled excavators.



## EQUIPMENT INFORMATION

Considering purchasing equipment? View the brochures that you are interested in, compare the specifications of the equipment, and request a quotation from your local dealer.



## ONLINE PARTS SHOP

Helps you purchase quality-proven genuine parts quickly. You can order quickly and easily the parts you need by searching for the right parts for your equipment.

## MY MACHINE

You can check all equipment data and maintenance costs easily and conveniently via the easy-to-use Dashboard.


## CUSTOMIZED SERVICE

Receive push notification alerts when equipment requires attention and manage your machine effectively with a checklist according to the product life cycle. You can request service directly and check the progress.

## SOCIAL MEDIA WALL

Enjoy the moment with Develon Construction equipment!

**DISCOVER MORE:**



DOOSAN Infracore Europe s.r.o.  
IBC - Pobřežní 620/3, 186 00 Praha 8-Karlín  
Czech Republic

©2023 DEVELON D4600683-EN (03-23)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice.

Specification(s) for your individual Develon equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Develon units may show other than standard equipment.

**DEVELON**